

# ES400B

## 1.General Description

ES400B is a 4G (Cat.M & NB2) GPS Tracker for vehicle with BLE. It reports location information via TCP/UDP with configurable intervals.



## 2.Main Functions

- **Tracking:** Send GPS information to server with configurable report interval
- **Power Saving Mode:** Device enters sleep mode when vehicle engine is OFF
- **Engine on/off Detection:** Detect engine on/off via detecting method by vibration
- **Driving Behavior Detection:** Report harsh braking, harsh acceleration and impact
- **Trip Start and Trip End Detection:** Report trip start and trip end
- **Tamper Alert:** Send tamper alert if the power supply is disconnected
- **Storing Messages:** Store messages if out of cellular coverage
- **Geofence:** It supports circle setting
- **BLE:** Communicate CAN data with the sub-device ES210
- **OTA (Over the Air):** Firmware can be remotely upgraded

## 3. Specification

### Physical and Electrical

Dimensions: 90mm\*55mm\*18mm

Weight: 65g

Battery Capacity: 300mAh

Supply Voltage: 6VDC ~ 42VDC

Power Consumption:

-Active Mode: < 42mA @12VDC

-Deep Sleep Mode: < 3mA @12VDC

Operation Temperature: -20℃ to 65℃

Storage Temperature: -20℃ to 65℃

LTE Module: Quectel BG95

Antenna: Built-in cellular, BLE and GPS

LED Indicators: 2 for GPS and cellular

SIM Card: Micro SIM(3FF)

### GPS Specifications

Sensitivity Tracking: -157dBm

Position Accuracy (CEP 50): <2.5m(Open Sky)

### Cellular Communication

Cat.M1 & NB2:

**Cat.M1/LTE-FDD:**

B1/B2/B3/B4/B5/B8/B12/B13/B18/B19/B20  
/B25/B26/B27/B28/B66/B85

**Cat NB2:**

B1/B2/B3/B4/B5/B8/B12/B13/B18/B19/B20  
/B25/B28/B66/B71/B85

### Protocol

HTTP/TCP/UDP/SMS/MQTT